

# Transportation Impact Study

PROPOSED
TRANSPORTATION
TERMINAL/TRAILER
PARKING FACILITY
DEVELOPMENT

5961 County Road 34 Township of South Glengarry, United Counties of Stormont-Dundas-Glengarry, Ontario

November 20, 2024 Project No: NT-23-206

#### 520 Industrial Parkway South, Suite 201

Aurora ON L4G 6W8



Phone: 905-503-2563 www.nextrans.ca

NextEng Consulting Group Inc.

November 20, 2024

1733286 Ontario Inc. 1221 North Service Road East Oakville, ON L6H 1A7

Attention: Ken Gill

Re: Transportation Impact Study

Proposed Transportation Terminal/Trailer Parkinng Facility Development

5961 County Road 34, Township of South Glengarry

Our Project No. NT-23-206

NexTrans Consulting Engineers (a Division of NextEng Consulting Group Inc.) is pleased to present the enclosed Transportation Impact Study for the above noted site in support of Official Plan and Zoning By-law Amendment Applications for a proposed transportation terminal/trailer parking facility development.

The subject lands are located south of Concession Road 1 and east of County Road 34 and are municipally addressed as 5961 County Road 34, in the Township of South Glengarry, United Counties of Stormont-Dundas-Glengarry, Ontario. The existing subject lands will be redeveloped to construct a transportation terminal with 270m<sup>2</sup> GFA and associated repair bay with 312m<sup>2</sup> GFA. A total of 139 truck/trailer parking spaces will be provided on-site, as well as 11 automobile parking spaces. Vehicular access is envisioned via a full movement driveway onto County Road 34.

The results of the capacity analysis indicate that the proposed development will have a negligible traffic impact to the surrounding road network. We trust the enclosed sufficiently addresses your needs. Should you have any questions, please do not hesitate to contact the undersigned.

Approved by:

Yours truly,

#### **NEXTRANS CONSULTING ENGINEERS**

Prepared by:

Listian Ariles

Kristian Aviles, B.Eng. Richard Pernicky, MITE

Transportation Analyst Principal

Issues and Revisions Registry

Identification	Date	Description of issued and/or revision
Final Report	November 20, 2024	For first submission

#### **EXECUTIVE SUMMARY**

NexTrans Consulting Engineers (a Division of NextEng Consulting Group Inc.) is pleased to present the enclosed Transportation Impact Study for the above noted site in support of Official Plan and Zoning By-law Amendment Applications for a proposed transportation terminal/trailer parking facility development.

# **Development Proposal**

The subject lands are located south of Concession Road 1 and east of County Road 34 and are municipally addressed as 5961 County Road 34, in the Township of South Glengarry, United Counties of Stormont-Dundas-Glengarry, Ontario. The existing subject lands will be redeveloped to construct a transportation terminal with 270m<sup>2</sup> GFA and associated repair bay with 312m<sup>2</sup> GFA. A total of 139 truck/trailer parking spaces will be provided on-site, as well as 11 automobile parking spaces. Vehicular access is envisioned via a full movement driveway onto County Road 34.

# **Capacity Analysis**

Based on the trip generation calculations, the proposed development is projected to generate a total of 18 two-way trips during AM peak hour (nine (9) inbound and nine (9) outbound) and 49 two-way trips during PM peak hour (27 inbound and 22 outbound).

Under future total traffic conditions, all movements of the study area intersection analyzed, as well as the proposed site access onto County Road 34 are projected to operate with residual capacity, with excellent levels of service, and with manageable delay and gueue lengths during both AM and PM peak hour.

# **Parking Review**

Based on the rates prescribed in the governing zoning by-law for the proposed land use, the proposed development requires a minimum of 11 vehicle parking spaces. In comparison to the supply of 11 vehicle parking spaces proposed on-site, the proposed parking supply is compliant with the minimum requirements of the governing zoning by-law.

## **Vehicular Maneuverability Review**

Given the proposed land use of transportation terminal/truck parking facility, the vehicle template for a WB-20 (TAC-2017) truck + trailer was used to confirm the maneuverability of the study and the swept path analysis demonstrates that the design vehicle can maneuver through the site unencumbered.

# **TABLE OF CONTENTS**

1.0	INTRODUCTION	1
	1.1. Study Approach	2
2.0	EXISTING TRAFFIC CONDITIONS	3
	2.1. Existing Road Network	3
	2.2. Existing Active Transportation Network	
	2.3. Existing Transit Facilities	4
	2.4. Existing Traffic Volumes	4
	2.5. Existing Traffic Assessment	4
3.0	FUTURE BACKGROUND CONDITIONS	5
	3.1. Future Corridor Growth	5
	3.2. Future Background Traffic Assessment	5
4.0	SITE TRAFFIC	6
	4.1. ITE Trip Generation	6
	4.2. Trip Distribution	7
5.0	FUTURE TOTAL ANALYSIS	8
	5.1. Future Total Traffic Assessment	8
	5.2. Left Turn Lane Warrant Analysis	9
6.0	PARKING ASSESSMENT	9
	6.1. Parking Requirements	9
	6.1.1. Vehicle Parking Requirements	9
7.0	SITE PLAN REVIEW	9
	7.1. Site Circulation	9
8.0	CONCLUSION	10
	8.1. Study Findings	
	8.2. Study Conclusions and Recommendations	

#### **LIST OF FIGURES**

Figure 1-1 – Subject Site Location

Figure 1-2 – Proposed Site Plan

Figure 2-1 – Existing Lane Configuration

Figure 2-2 – Existing Traffic Volumes

Figure 3-1 – Future Background Traffic Volumes

Figure 4-1 – Site Traffic Volumes

Figure 5-1 – Future Total Traffic Volumes

Figure 7-1 - AutoTURN Maneuverability Analysis (WB-20 TAC-2017)

#### **LIST OF TABLES**

Table 2.1: Traffic Data Collection Summary

Table 2.2 – Level of Service – Existing Traffic Assessment

Table 3.1 – Future Background Traffic Assessment

Table 4.1 – Table 4.1 – Proxy Site Turning Movement Counts

Table 4.1 – Site Traffic Trip Generation

Table 4.2 – Site Traffic Trip Distribution

Table 5.1 – Level of Service – Future Total Traffic Assessment

Table 6.1 – Vehicle Parking Requirements (Zoning By-law 2014-070 Section 4.25)

#### **APPENDICES**

Appendix A – Site Plan

Appendix B – Terms of Reference

Appendix C – Traffic Data

Appendix D – Existing Traffic Conditions – Capacity Analysis Results

Appendix E – Future Background Traffic Conditions – Capacity Analysis Results

Appendix F – Proxy Site Turning Movement Counts

Appendix G – Future Total Traffic Conditions – Capacity Analysis Results


Appendix H – Left Turn Lane Warrant



# 1.0 INTRODUCTION

Nextrans Consulting Engineers (A Division of NextEng Consulting Group Inc.) was retained by 1733286 Ontario Inc. (the 'Client') to undertake a Transportation Impact Study in support of Official Plan and Zoning By-law Amendment applications for a proposed transportation terminal/trailer parking facility development.

The subject lands are located south of Concession Road 1 and east of County Road 34, municipally addressed as 5961 County Road 34 in the Township of South Glengarry, United Counties of Stormont-Dundas-Glengarry, Ontario. The location of the proposed development is illustrated in **Figure 1**.



The development proposal is to redevelop the existing subject lands to construct a transportation terminal with 270m<sup>2</sup> GFA and associated repair bay with 312m<sup>2</sup> GFA. A total of 139 truck/trailer parking spaces will be provided on-site, as well as 11 automobile parking spaces. Vehicular access is envisioned via a full movement driveway onto County Road 34.

The proposed site plan is illustrated in Figure 1-2 and provided in full detail in Appendix A.





Figure 1-2 - Proposed Site Plan

# 1.1. Study Approach

The weekday morning (AM) and weekday afternoon (PM) peak traffic periods were assessed. A baseline year of 2024 was considered for baseline conditions. For the purposes of this study, a five (5)-year horizon from baseline was assessed for a horizon year of 2029.

It is to be noted that a terms of reference was provided to the United Counties of Stormont-Dundas-Glengarry; however, no response was received within the timeline that this report was prepared. The terms of reference is enclosed in **Appendix B**.




#### 2.0 EXISTING TRAFFIC CONDITIONS

# 2.1. Existing Road Network

The existing road network, lane configuration and existing traffic control for the study area are described below.

- County Road 34 is a north-south arterial road that is governed by the United Counties of Stormont-Dundas-Glengarry. County Road 34 operates with a two (2)-lane cross section (one (1)-travel lane per direction) in the vicinity of the study area, and maintains a posted speed limit of 80 km/h.
- Concession Road 1 is an east-west arterial road. Peterborough County Road 36 operates with a two (2)-lane cross section (one (1)-travel lane per direction) in the vicinity of the study area. It generally maintains a posted speed limit of 50 km/h.

Existing road network lane configurations are illustrated in Figure 2-1.



# 2.2. Existing Active Transportation Network

#### **Sidewalks**

Currently, there are no sidewalks available within the comfortable walking distance from the subject site.

### Cycling

Currently, there are no cycling facilities available within the surrounding area of the subject site.



# 2.3. Existing Transit Facilities

Currently, there are no existing transit facilities available within the surrounding area of the subject site.

# 2.4. Existing Traffic Volumes

Weekday morning and afternoon peak period turning movement counts (TMC) were undertaken by Spectrum Traffic for the study area intersection during the weekday AM and PM peak periods. TMC data is enclosed **Appendix C**. A summary of traffic data collection is provided in **Table 2.1**.

**Table 2.1: Traffic Data Collection Summary** 

Intersection	Source	Survey Date
County Road 34 & Concession Road 1	Spectrum Traffic Inc.	December 6, 2023


# 2.5. Existing Traffic Assessment

It is noted that the peak hour factor (PHF) was calculated for the study area intersection for both AM and PM peak hours. The calculated PHF was carried forward in all future scenarios as well. Peak hour factors were calculated and applied per intersection using the following equation:

$$PHF = \frac{total\ peak\ hour\ volume}{4*peak\ 15\ minute\ volume}$$

Baseline existing traffic volumes are illustrated in Figure 2-2.







The baseline existing traffic volumes were analyzed using Synchro 10 in accordance with the methodology outlined in the highway Capacity Manual (HCM 2000) published by the Transportation Research Board. The detailed results are enclosed in **Appendix D** and summarized in **Table 2.2**.

Table 2.2 – Level of Service – Existing Traffic Assessment

		W	/eekday A	M Peak H	our	Weekday PM Peak Hour									
Intersection	Movement	v/c	Delay (s)	LOS	Queue 95 <sup>th</sup>	v/c	Delay (s)	LOS	Queue 95 <sup>th</sup>						
	Unsignalized Intersections														
County Road 34 & Concession Road 1	WBLR	0.00	10.1	В	0	0.00	0.0	A	0						

Based on the results of the capacity analysis under existing traffic conditions, the study area intersection currently operate with residual capacity (i.e., volume to capacity ratio or V/C < 1.00), with excellent levels of service and with minimal delay and queue lengths during both AM and PM peak hours.


#### 3.0 FUTURE BACKGROUND CONDITIONS

#### 3.1. Future Corridor Growth

In lieu of the availability of historical AADT data within the study area, a conservative 2% growth rate per annum was applied to the through volumes of County Road 34 to model future traffic growth within the area. Given that Concession Road 1 is a low volume collector road, no growth was applied.

# 3.2. Future Background Traffic Assessment

The estimated future background traffic volumes are illustrated in Figure 3-1.





The detailed Synchro capacity analysis results for future are summarized in **Table 3.1** and the detailed reports are enclosed in **Appendix E**.

Table 3.1 - Future Background Traffic Assessment

		W	eekday A	M Peak H	our	Weekday PM Peak Hour									
Intersection	Movement	v/c	Delay (s)	LOS	Queue 95 <sup>th</sup>	v/c	Delay (s)	1 1 05							
	Unsignalized Intersections														
County Road 34 & Concession Road 1	WBLR	0.00	10.3	В	0	0.00	0.0	Α	0						

Based on the results of the capacity analysis under future background traffic conditions, the study area intersection is projected to operate with residual capacity (i.e., volume to capacity ratio or V/C < 1.00), with excellent levels of service and with manageable delay and gueue lengths during both AM and PM peak hours.

## 4.0 SITE TRAFFIC

# 4.1. ITE Trip Generation

The development proposal is to redevelop to construct a transportation terminal with 270m<sup>2</sup> GFA and associated repair bay with 312m<sup>2</sup> GFA. A total of 139 truck/trailer parking spaces will also be provided on-site. Typically, the *Trip Generation Manual, 11th Edition* published by the Institute of Transportation Engineers (ITE) is used to determine the number of trips that a site will generate; however, the trip generation manual does not contain information for transportation terminals/truck parking facilities.

In lieu of information available in the ITE Trip Generation Manual, Nextrans used turning movement count data that was collected at a proxy site located in the Town of Caledon, which has the same land use as the proposed development, the proxy site is municipally addressed as 6186 Mayfield Road and accommodates both truck and truck + trailer parking and has a repurposed detached house that operates as an office. The proxy site has an approximate lot area of 5.52 ha (13.65 ac). The proxy site trip generation surveys were conducted on September 21, 2023, and September 22, 2023 during morning peak period (7:00AM – 9:00AM) and afternoon peak period (4:00PM – 6:00PM).

The results of the proxy site trip generation surveys are summarized in **Appendix F** and the peak hour trip generation results from each day of surveys are detailed below in **Table 4.1**.

Table 4.1 – Table 4.2 – Proxy Site Turning Movement Counts

Time Period	Parameter	Sej	otember 21, 20	)23	September 22, 2023					
	Faranietei	Inbound Outbound Total		Inbound	Outbound	Total				
AM Peak	Gross Trips	9	7	16	9	9	18			
Period	Trip Rate	1.63	1.27	2.90	1.63	1.63	3.26			
PM Peak	Gross Trips	28	23	51	28	12	40			
Period	Trip Rate	5.07	4.17	9.24	5.07	2.17	7.25s			

The peak number of trips generated by the proxy site during AM peak hour occurred on the second survey day, with a total of 18 two-way trips or <u>3.26 trips/ha</u>.

The peak number of trips generated by the proxy site during PM peak hour occurred on the first survey day, with a total of 51 two-way trips or **9.24 trips/ha**.



Trip rates were prorated to account for the difference in size between the proxy site and the subject site. It is to be noted that the net developable site area is 2.4ha; however, as a conservative approach, the total site area of 5.36ha was instead considered. The prorated trip generation for the subject site is detailed in **Table 4.2**.

Table 4.3 – Site Traffic Trip Generation

Parameter		AM Peak Hour		PM Peak Hour				
Parameter	Inbound	Outbound	Total	Inbound	Outbound	Total		
Gross Trips	9	9	18	27	22	49		

Based on the trip generation calculations, the proposed development is projected to generate a total of 18 two-way trips during AM peak hour (nine (9) inbound and nine (9) outbound) and 49 two-way trips during PM peak hour (27 inbound and 22 outbound).


## 4.2. Trip Distribution

The assumptions for trip distribution rates are based on the distributional splits of existing TMC data within the study area road network, as well as engineering judgement for routes that drivers would likely take to and from the site access. Trip distribution is summarized in **Table 4.2** and trip assignment is illustrated in **Figure 4-1**.

**Table 4.4 – Site Traffic Trip Distribution** 

Corridor	Direction	А	M	PM					
Corridor	Direction	Inbound	Outbound	Inbound	Outbound				
County	N	47%	53%	48%	52%				
Road 34	S	53%	47%	52%	48%				
Total		100%	100%	100%	100%				

Figure 4-1 – Site Traffic Volumes





#### 5.0 **FUTURE TOTAL ANALYSIS**

#### 5.1. **Future Total Traffic Assessment**

The forecasted future total traffic volumes are defined as the sum of the distributed site-generated traffic and future background traffic volumes. The future total traffic volumes are illustrated in Figure 5-1.




Figure 5-1 – Future Total Traffic Volumes

The capacity analysis results are summarized in Table 5.1 and detailed reports are provided in Appendix G.

Weekday PM Peak Hour Weekday AM Peak Hour Intersection Movement Delay Queue Delay Queue LOS LOS v/c v/c 95th 95th (s) (s) **Unsignalized Intersections** County Road 34 & **WBLR** 0.00 10.3 В 0.0 0.00 0.0 Α 0.0 Concession Road 1 WBLR 0.01 9.6 Α 0.3 0.03 10.2 В 8.0 County Road 34 & Site Access **SBLT** 0.00 0.2 Α 0.1 0.01 0.7 Α 0.2

Table 5.1 - Level of Service - Future Total Traffic Assessment

Under future total traffic conditions, all movements of the study area intersection analyzed, as well as the proposed site access onto County Road 34 are projected to operate with residual capacity, with excellent levels of service, and with manageable delay and queue lengths during both AM and PM peak hour.

As such, the projected site traffic generated by the proposed development will have a negligible impact to the future operations of the study area road network.



# 5.2. Left Turn Lane Warrant Analysis

The MTO Design Supplement for TAC Geometric Design Guide for Canadian Roads, April 2020, was reviewed to determine if left turn lanes are warranted on County Road 34 at the proposed site access.

For the purposes of this assessment, future total PM traffic volumes were used as this would provide a more conservative analysis in comparison to the use of future total AM traffic volumes. The following parameters were used to conduct the analysis:

 $V_A$  = 172 vehicles  $V_O$  = 188 vehicles  $W_O$  of advancing vehicles turning left = 7.5% Design Speed = 90 km/h (posted 80 km/h + 10 km/h)

An excerpt of the MTO Design Supplement is enclosed in **Appendix H** that illustrates the above parameters.

Based on Exhibit 9A-19 of the MTO Design Supplement, auxiliary left turn lanes are not warranted for the proposed site access.

#### 6.0 PARKING ASSESSMENT

# 6.1. Parking Requirements

## 6.1.1. Vehicle Parking Requirements

The subject lands are subject to the parking requirements stipulated within the Township of South Glengarry's Zoning By-law No. 38-09. Given that the proposed development consists of a transportation terminal and a repair bay, only the GFA of the transportation terminal was considered in the calculation of the minimum parking requirement. The technical parking requirement is detailed in **Table 6.1**.

Table 6.1 – Vehicle Parking Requirements (Zoning By-law 2014-070 Section 4.25)

Land Use*	GFA	Parking Rate	Min. Parking Requirement	Parking Supply
All other uses not listed above	59	1 space / 25m <sup>2</sup>	11 spaces	11 spaces

<sup>\*</sup> As stipulated in the zoning by-law

Based on the rates prescribed in the governing zoning by-law for the proposed land use, the proposed development requires a minimum of 11 vehicle parking spaces. In comparison to the supply of 11 vehicle parking spaces proposed on-site, the proposed parking supply is compliant with the minimum requirements of the governing zoning by-law.

#### 7.0 SITE PLAN REVIEW

#### 7.1. Site Circulation

AutoTURN software was used to generate a vehicular turning template to confirm and demonstrate the accessibility of the proposed study area. Given the proposed land use of transportation terminal/truck parking facility, the vehicle template for a WB-20 (TAC-2017) truck + trailer was used to confirm the maneuverability of the study and the swept path analysis demonstrates that the design vehicle can maneuver through the site unencumbered.

The AutoTURN analysis is illustrated in Figure 7-1.



#### 8.0 CONCLUSION

# 8.1. Study Findings


The findings of our analysis are as follows:

- The development proposal is to redevelop the existing subject lands to construct a transportation terminal
  with 270m² GFA and associated repair bay with 312m² GFA. A total of 139 truck/trailer parking spaces will be
  provided on-site, as well as 11 automobile parking spaces. Vehicular access is envisioned via a full movement
  driveway onto County Road 34.
- Based on the results of the capacity analysis under existing traffic conditions, all study area intersections
  currently operate with residual capacity (i.e., volume to capacity ratio or V/C < 1.00), with excellent levels of
  service and with minimal delay and gueue lengths during both AM and PM peak hours.</li>
- Based on the results of the capacity analysis under future background traffic conditions, all study area
  intersections are projected to operate with residual capacity (i.e., volume to capacity ratio or V/C < 1.00), with
  excellent levels of service and with minimal delay and queue lengths during both AM and PM peak hours.</li>
- Based on the trip generation calculations, the proposed development is projected to generate a total of 18 two-way trips during AM peak hour (nine (9) inbound and nine (9) outbound) and 49 two-way trips during PM peak hour (27 inbound and 22 outbound).
- Under future total traffic conditions, all movements of the study area intersection analyzed, as well as the
  proposed site access onto County Road 34 are projected to operate with residual capacity, with excellent
  levels of service, and with manageable delay and queue lengths during both AM and PM peak hour.
- The MTO Design Supplement was reviewed to determine if auxiliary left turn lanes are warranted at the proposed site access. Based on the assessment, the warrants for an auxiliary left turn lane are not warranted.
- Based on the rates prescribed in the governing zoning by-law for the proposed land use, the proposed development requires a minimum of 11 vehicle parking spaces. In comparison to the supply of 11 vehicle parking spaces proposed on-site, the proposed parking supply is compliant with the minimum requirements of the governing zoning by-law.
- Given the proposed land use of transportation terminal/truck parking facility, the vehicle template for a WB-20
  (TAC-2017) truck + trailer was used to confirm the maneuverability of the study and the swept path analysis
  demonstrates that the design vehicle can maneuver through the site unencumbered.

# 8.2. Study Conclusions and Recommendations

Based on the findings of our analysis, our conclusions and recommendations are as follows:

- The projected site traffic generated by the proposed development will have a negligible impact to the future operations of the study area road network.
- Based on the assessments completed in this study, auxiliary turning lanes are not required to support the development site traffic generated by the subject site.
- The proposed parking supply is compliant with the minimum requirements of the governing zoning by-law.
- The site plan is accessible for the intended design vehicles.




KEY PLAN

	$\overline{}$
DESIGN BY: K.A.	DATE: February 21, 2024
CHECKED BY: R.P.	PROJECT NO.
DRAWN BY: K A	─ <b>I</b> NT-23-206
100	DRAWING NO.
SCALE: NTS	
	Figure 7-1



# Appendix A – Site Plan





# **Appendix B – Terms of Reference**

#### 520 Industrial Parkway South, Suite 201 Aurora, Ontario L4G 6W8

Phone: 905-503-2563 www.nextrans.ca



**To:** Benjamin de Haan, United Counties of Stormont, Dundas and Glengarry

From: Kristian Aviles, Nextrans Consulting Engineers

Date: November 21, 2023

Re: Terms of Reference – Transportation Impact Study

**Proposed Transportation Depot and Truck / Trailer Parking Facility** 

5961 County Road 34, South Glengarry

Our Project No. NT-23-206

#### INTRODUCTION

We wish to confirm the following work plan for a Transportation Impact Study for a proposed transportation depot and truck / trailer parking facility located east of County Road 34 and south of Concession Road 2, (herein referred to as the "subject site"), in Town of South Glengarry. The subject site is designated in Zoning By-law 06-2023 as AG for agricultural. The proposed site plan is enclosed in **Appendix A** of this Terms of Reference. **Figure 1** illustrates the location of the subject site.



Figure 1: Subject Site Location

## **STUDY AREA**

Nextrans proposes to collect turning movement count (TMC) data at the following study area intersections during AM (7:00 AM – 10:00 AM) and PM (4:00 PM – 7:00 PM) peak periods:

- 1. County Road 34 & Concession Road 1 (unsignalized)
- 2. County Road 34 & Site Access (unsignalized)

#### **BACKGROUND TRAFFIC**

#### **General Corridor Growth Rate**

Historical AADT data will be reviewed and Nextrans will consult with The United Counties of Stormont, Dundas & Glengarry to determine corridor growth rates. In lieu of the availability of historical AADT, Nextrans proposes to use a conservative growth rate of 2% per annum.

#### **Road Network Improvements**

Nextrans will note any road network improvements identified within the study area and account for any traffic diversions associated with these improvements within in our analysis.

#### **Background Development Traffic**

Nextrans requests that the United Counties of Stormont, Dundas and Glengarry provide the relevant traffic studies for background developments required for consideration in our study.

#### TRIP GENERATION, DISTRIBUTION, & ASSIGNMENT

Nextrans' standard approach in determining the projected number of trips that a proposed development will generate is to use the Institute of Transportation Engineers (ITE) Trip Generation Manual, 11<sup>th</sup> Edition; however, the ITE Trip Generation Manual does not contain information for the proposed land use.

Nextrans has previously prepared Transportation Impact Studies for development proposals within the GTA similar to the proposed land use of the subject site. Our methodology to determine trip generation for the aforementioned developments was to conduct proxy site surveys of existing, operational truck parking facilities to determine an applicable trip rate based on lot size. As such, Nextrans proposes to apply the trip rates obtained from proxy sites to project the number of trips that the proposed development will generate.

The general trip distribution will be based on existing TMC data and trip assignment will be completed to reflect the configuration of the proposed site access, turning restrictions, and logical routings.

#### **FUTURE TRAFFIC SCENARIOS**

Future background and future total analyses for the study area intersections will be conducted over a five (5)-year horizon from present year. Given that this report will be prepared at the end of 2023, a future analysis year of 2029 will be analyzed.

#### REMEDIAL MEASURES

Under future total conditions, any through or shared through/turning movements at the studied intersections that exceed a V/C ratio of 0.90 or exclusive movements that exceed a V/C ratio of 1.00 will be identified. If remedial actions such as signal optimization are unsuccessful this will also be identified. If remedial measures are to be employed, a scenario will be provided demonstrating the change in intersection operations.

# **PARKING & LOADING**

The site is currently subject to The Corporation of the Township of South glengarry By-law 06-2023, which will be reviewed for parking and loading requirements.

We trust the enclosed sufficiently addresses your needs. Should you have any questions, please do not hesitate to contact the undersigned.


Yours truly,

**NEXTRANS CONSULTING ENGINEERS** 

Kristian Aviles, B.Eng Transportation Analyst

Listian Ariles

Appendix A – Site Plan





# **Appendix C – Traffic Data**

# Turning Movement Count Location Name: COUNTY RD 34 & CONCESSION RD 1 Date: Wed, Dec 06, 2023 Deployment Lead: David Chu

NexTrans SUITE 204 15260 YONGE ST AURORA ONTARIO, L4G 1N4 CANADA

					Turi	ning Mov	ement (	Count (1	. COUN	TY RD 34 & CONCI	ESSION	RD 1)					
Chaut Time				<b>hbound</b> TY RD 34					tbound SSION RE	) 1				nbound TY RD 34		Int. Total (15 min)	Int. Total (1 hr)
Start Time	Thru N:S	Left N:E	UTurn N:N	Peds N:	Approach Total	Right E:N	Left E:S	UTurn E:E	Peds E:	Approach Total	Right S:E	Thru S:N	UTurn S:S	Peds S:	Approach Total		
07:00:00	23	0	0	0	23	0	0	0	0	0	0	14	0	0	14	37	
07:15:00	30	0	0	0	30	0	0	0	0	0	0	25	0	0	25	55	
07:30:00	31	0	0	0	31	0	0	0	0	0	0	40	0	0	40	71	
07:45:00	23	0	0	0	23	0	0	0	0	0	0	29	0	0	29	52	215
08:00:00	28	0	0	0	28	0	1	0	0	1	0	27	0	0	27	56	234
08:15:00	33	0	0	0	33	0	0	0	0	0	0	35	0	0	35	68	247
08:30:00	24	0	0	0	24	0	0	0	0	0	0	26	0	0	26	50	226
08:45:00	28	0	0	0	28	0	0	0	0	0	0	21	0	0	21	49	223
09:00:00	26	0	0	0	26	0	0	0	0	0	0	19	0	0	19	45	212
09:15:00	20	0	0	0	20	0	0	0	0	0	0	27	0	0	27	47	191
09:30:00	30	0	0	0	30	0	0	0	0	0	0	23	0	0	23	53	194
09:45:00	32	0	0	0	32	0	0	0	0	0	0	30	0	0	30	62	207
***BREAK	***															-	
16:00:00	43	0	0	0	43	0	0	0	0	0	1	39	1	0	41	84	
16:15:00	37	0	0	0	37	0	0	0	0	0	0	51	0	0	51	88	
16:30:00	35	0	0	0	35	0	0	0	0	0	0	30	0	0	30	65	
16:45:00	29	0	0	0	29	0	0	0	0	0	0	37	0	0	37	66	303
17:00:00	42	0	0	0	42	0	0	0	0	0	0	33	0	0	33	75	294
17:15:00	31	1	0	0	32	0	0	0	0	0	0	35	0	0	35	67	273
17:30:00	38	0	0	0	38	0	0	0	0	0	0	27	0	0	27	65	273
17:45:00	22	0	0	0	22	0	0	0	0	0	0	18	0	0	18	40	247
18:00:00	19	0	0	0	19	0	0	0	0	0	0	21	0	0	21	40	212
18:15:00	14	0	0	0	14	0	0	0	0	0	0	12	0	0	12	26	171
18:30:00	15	0	0	0	15	0	0	0	0	0	0	12	0	0	12	27	133
18:45:00	13	0	0	0	13	0	0	0	0	0	0	18	0	0	18	31	124
Grand Total	666	1	0	0	667	0	1	0	0	1	1	649	1	0	651	1319	-
Approach%	99.9%	0.1%	0%		-	0%	100%	0%		-	0.2%	99.7%	0.2%		-	-	-
Totals %	50.5%	0.1%	0%		50.6%	0%	0.1%	0%		0.1%	0.1%	49.2%	0.1%		49.4%	-	-
Heavy	57	0	0		-	0	0	0		-	0	60	0		-	-	-
Heavy %	8.6%	0%	0%		-	0%	0%	0%		-	0%	9.2%	0%		-	-	-
Bicycles	-	-	-		-	-	-	-		-	-	-	-		-	-	-
Bicycle %	-	-	-		-	-	-	-		-	-	-	-		-	-	-

# Turning Movement Count Location Name: COUNTY RD 34 & CONCESSION RD 1 Date: Wed, Dec 06, 2023 Deployment Lead: David Chu

NexTrans SUITE 204 15260 YONGE ST AURORA ONTARIO, L4G 1N4 CANADA

					Peak Hour: 07:3	30 AM - 0	08:30 AM	Weath	ner: Ove	rcast Clouds (-7.99	9 °C)					
Start Time	Southbound COUNTY RD 34						<b>Westbound</b> CONCESSION RD 1						<b>Northbound</b> COUNTY RD 34			
	Thru	Left	UTurn	Peds	Approach Total	Right	Left	UTurn	Peds	Approach Total	Right	Thru	UTurn	Peds	Approach Total	
07:30:00	31	0	0	0	31	0	0	0	0	0	0	40	0	0	40	71
07:45:00	23	0	0	0	23	0	0	0	0	0	0	29	0	0	29	52
08:00:00	28	0	0	0	28	0	1	0	0	1	0	27	0	0	27	56
08:15:00	33	0	0	0	33	0	0	0	0	0	0	35	0	0	35	68
Grand Total	115	0	0	0	115	0	1	0	0	1	0	131	0	0	131	247
Approach%	100%	0%	0%		-	0%	100%	0%		-	0%	100%	0%		-	•
Totals %	46.6%	0%	0%		46.6%	0%	0.4%	0%		0.4%	0%	53%	0%		53%	-
PHF	0.87	0	0		0.87	0	0.25	0		0.25	0	0.82	0		0.82	-
Heavy	6	0	0		6	0	0	0		0	0	21	0		21	-
Heavy %	5.2%	0%	0%		5.2%	0%	0%	0%		0%	0%	16%	0%		16%	-
Lights	109	0	0		109	0	1	0		1	0	110	0		110	
Lights %	94.8%	0%	0%		94.8%	0%	100%	0%		100%	0%	84%	0%		84%	-
Single-Unit Trucks	2	0	0		2	0	0	0		0	0	8	0		8	-
Single-Unit Trucks %	1.7%	0%	0%		1.7%	0%	0%	0%		0%	0%	6.1%	0%		6.1%	-
Buses	2	0	0		2	0	0	0		0	0	3	0		3	-
Buses %	1.7%	0%	0%		1.7%	0%	0%	0%		0%	0%	2.3%	0%		2.3%	-
Articulated Trucks	2	0	0		2	0	0	0		0	0	10	0		10	-
Articulated Trucks %	1.7%	0%	0%		1.7%	0%	0%	0%		0%	0%	7.6%	0%		7.6%	-


# Turning Movement Count Location Name: COUNTY RD 34 & CONCESSION RD 1 Date: Wed, Dec 06, 2023 Deployment Lead: David Chu

NexTrans SUITE 204 15260 YONGE ST AURORA ONTARIO, L4G 1N4 CANADA

					Peak Hour: 0	4:00 PM	- 05:0	OPM W	/eather:	Broken Clouds (-7	°C)					
Start Time				thbound NTY RD 34					estbound ESSION R	D 1				ibound TY RD 34		Int. Total (15 min)
	Thru	Left	UTurn	Peds	Approach Total	Right	Left	UTurn	Peds	Approach Total	Right	Thru	UTurn	Peds	Approach Total	
16:00:00	43	0	0	0	43	0	0	0	0	0	1	39	1	0	41	84
16:15:00	37	0	0	0	37	0	0	0	0	0	0	51	0	0	51	88
16:30:00	35	0	0	0	35	0	0	0	0	0	0	30	0	0	30	65
16:45:00	29	0	0	0	29	0	0	0	0	0	0	37	0	0	37	66
Grand Total	144	0	0	0	144	0	0	0	0	0	1	157	1	0	159	303
Approach%	100%	0%	0%		-	0%	0%	0%		-	0.6%	98.7%	0.6%		-	-
Totals %	47.5%	0%	0%		47.5%	0%	0%	0%		0%	0.3%	51.8%	0.3%		52.5%	-
PHF	0.84	0	0		0.84	0	0	0		0	0.25	0.77	0.25		0.78	-
Heavy	15	0	0		15	0	0	0		0	0	4	0		4	•
Heavy %	10.4%	0%	0%		10.4%	0%	0%	0%		0%	0%	2.5%	0%		2.5%	-
Lights	129	0	0		129	0	0	0		0	1	153	1		155	-
Lights %	89.6%	0%	0%		89.6%	0%	0%	0%		0%	100%	97.5%	100%		97.5%	-
Single-Unit Trucks	5	0	0		5	0	0	0		0	0	1	0		1	-
Single-Unit Trucks %	3.5%	0%	0%		3.5%	0%	0%	0%		0%	0%	0.6%	0%		0.6%	-
Buses	3	0	0		3	0	0	0		0	0	1	0		1	-
Buses %	2.1%	0%	0%		2.1%	0%	0%	0%		0%	0%	0.6%	0%		0.6%	-
Articulated Trucks	7	0	0		7	0	0	0		0	0	2	0		2	-
Articulated Trucks %	4.9%	0%	0%		4.9%	0%	0%	0%		0%	0%	1.3%	0%		1.3%	-



(A) mapbox



34

© Mapbox © OpenStreetMap



#### Peak Hour: 04:00 PM - 05:00 PM Weather: Broken Clouds (-7 °C)





# **Appendix D – Existing Traffic Conditions – Capacity Analysis Results**

	1	1	1	~	1	Į
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	Y		1→			र्भ
Traffic Volume (veh/h)	1	0	131	0	0	115
Future Volume (Veh/h)	1	0	131	0	0	115
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Hourly flow rate (vph)	1	0	151	0	0	132
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	283	151			151	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	283	151			151	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	711	901			1442	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	1	151	132			
Volume Left	1	0	0			
Volume Right	0	0	0			
cSH	711	1700	1442			
Volume to Capacity	0.00	0.09	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	10.1	0.0	0.0			
Lane LOS	В	0.0	0.0			
Approach Delay (s)	10.1	0.0	0.0			
Approach LOS	В	0.0	0.0			
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliza	ation		16.9%	IC	U Level o	f Service
Analysis Period (min)			15	.0	2 201010	. 50. 1100
ranaryolo i onou (iliii)			10			

	1	•	1	~	/	ļ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		1→			ःसी
Traffic Volume (veh/h)	0	0	157	1	0	144
Future Volume (Veh/h)	0	0	157	1	0	144
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	0	0	183	1	0	167
Pedestrians				-		
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	350	184			184	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	350	184			184	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	<b>V.</b> .	V. <u>_</u>				
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	651	864			1403	
			05.4		1100	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	0	184	167			
Volume Left	0	0	0			
Volume Right	0	1	0			
cSH	1700	1700	1403			
Volume to Capacity	0.00	0.11	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	0.0	0.0	0.0			
Lane LOS	Α					
Approach Delay (s)	0.0	0.0	0.0			
Approach LOS	Α					
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliz	ation		11.7%	IC	U Level o	f Service
Analysis Period (min)			15	.0		
raidiyolo i criba (ililii)			10			



**Appendix E – Future Background Traffic Conditions - Capacity Analysis Results** 

	1	•	1	~	1	Į.
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		1→			ःसी
Traffic Volume (veh/h)	1	0	145	0	0	127
Future Volume (Veh/h)	1	0	145	0	0	127
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Hourly flow rate (vph)	1	0	167	0	0	146
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	313	167			167	
vC1, stage 1 conf vol	0.0	101				
vC2, stage 2 conf vol						
vCu, unblocked vol	313	167			167	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	<b>V.</b> 1	0.2				
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	684	882			1423	
			CD 4			
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	1	167	146			
Volume Left	1	0	0			
Volume Right	0	0	0			
cSH	684	1700	1423			
Volume to Capacity	0.00	0.10	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	10.3	0.0	0.0			
Lane LOS	В					
Approach Delay (s)	10.3	0.0	0.0			
Approach LOS	В					
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliza	ation		17.6%	IC	U Level o	of Service
Analysis Period (min)			15			
			10			

	1	1	1	~	1	ļ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	M		1→			ની
Traffic Volume (veh/h)	0	0	173	1	0	159
Future Volume (Veh/h)	0	0	173	1	0	159
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	0	0	201	1	0	185
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	386	202			202	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	386	202			202	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	621	844			1382	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	0	202	185			
Volume Left	0	0	0			
Volume Right	0	1	0			
cSH	1700	1700	1382			
Volume to Capacity	0.00	0.12	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	0.0	0.0	0.0			
Lane LOS	А					
Approach Delay (s)	0.0	0.0	0.0			
Approach LOS	Α					
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliza	ation		12.5%	IC	:Ul evel	of Service
Analysis Period (min)	G(1011		15	10	. S EGVOIC	OOI VIOO
Analysis i Gnou (IIIII)			IJ			



# **Appendix F – Proxy Site Turning Movement Counts**

#### 6186 Mayfield Road Trip Generation Survey Results

Ī										AM I	Peak									
Date					21-Se	p-23									22-Se	p-23				
Time			Inbound				-	OUTBOUND	)				Inbound					OUTBOUND	)	
Vehicle	CAR	SU TRUCK	TRUCK	JCK+TRAIL	TOTAL	CAR	SU TRUCK	TRUCK	UCK+TRAIL	TOTAL	CAR	SU TRUCK	TRUCK	JCK+TRAIL	TOTAL	CAR	SU TRUCK	TRUCK	UCK+TRAIL	TOTAL
7:00	2	1	0	1	4	0	1	1	0	2	1	1	2	1	5	0	2	2	0	4
7:15	0	1	1	0	2	0	0	0	1	1	0	0	1	1	2	0	0	1	1	2
7:30	0	0	1	1	2	1	2	0	0	3	1	0	0	0	1	1	0	0	1	2
7:45	0	0	1	0	1	0	0	0	1	1	1	0	0	0	1	0	0	1	0	1
8:00	1	0	1	0	2	0	0	1	1	2	0	1	2	0	3	1	2	1	0	4
8:15	0	0	1	0	1	1	0	0	0	1	1	0	1	0	2	0	0	0	1	1
8:30	1	1	0	0	2	1	0	0	1	2	1	1	0	0	2	0	0	2	1	3
8:45	1	0	1	1	3	0	0	1	0	1	0	0	0	1	1	0	0	0	0	0
Total 1-way			9					7					9					9		
Total 2-way					10	6									1	8				

										PM I	Peak									
Date					21-Se	ep-23									22-Se	p-23				
Time			Inbound					OUTBOUNI	)				Inbound					OUTBOUND	)	
Vehicle	CAR	SU TRUCK	TRUCK	JCK+TRAIL	TOTAL	CAR	SU TRUCK	TRUCK	UCK+TRAIL	TOTAL	CAR	SU TRUCK	TRUCK	JCK+TRAIL	TOTAL	CAR	SU TRUCK	TRUCK	UCK+TRAIL	TOTAL
16:00	3	0	1	1	5	2	0	1	0	3	1	0	2	0	3	1	0	0	0	1
16:15	2	4	1	0	7	3	0	1	0	4	1	1	2	1	5	1	0	1	0	2
16:30	0	2	1	1	4	2	0	0	0	2	4	2	3	3	12	1	0	2	1	4
16:45	2	1	2	1	6	2	0	0	0	2	0	1	2	1	4	0	0	1	1	2
17:00	3	4	0	3	10	6	1	2	0	9	2	0	2	3	7	1	0	1	1	3
17:15	4	3	1	0	8	4	0	1	1	6	3	1	1	0	5	0	2	1	0	3
17:30	1	3	1	3	8	3	0	1	0	4	2	1	3	2	8	0	1	1	0	2
17:45	0	1	1	0	2	3	0	0	1	4	1	0	1	0	2	0	0	0	2	2
Total 1-way			28					23					28					12		
Total 2-way					5	1									4	0				



# **Appendix G – Future Total Traffic Conditions - Capacity Analysis Results**

	•	•	<b>†</b>	<i>&gt;</i>	<b>&gt;</b>	<b>↓</b>
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		ĵ»			र्स
Traffic Volume (veh/h)	1	0	150	0	0	131
Future Volume (Veh/h)	1	0	150	0	0	131
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Hourly flow rate (vph)	1	0	172	0	0	151
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	323	172			172	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	323	172			172	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	675	877			1417	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total		172	151			
Volume Left	1		0			
	0	0	0			
Volume Right cSH	675	1700	1417			
Volume to Capacity	0.00	0.10	0.00			
Queue Length 95th (m)						
Control Delay (s)	10.3	0.0	0.0			
Lane LOS	B	0.0	0.0			
Approach LOS	10.3	0.0	0.0			
Approach LOS	В					
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliz	zation		17.9%	IC	U Level	of Service
Analysis Period (min)			15			

	•	•	<b>†</b>	~	<b>&gt;</b>	<b>↓</b>
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		ĵ.			ર્ન
Traffic Volume (veh/h)	4	5	145	5	4	128
Future Volume (Veh/h)	4	5	145	5	4	128
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	4	5	158	5	4	139
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	308	160			163	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	308	160			163	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	99	99			100	
cM capacity (veh/h)	687	890			1428	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	9	163	143			
Volume Left	4	0	4			
	5	5	0			
Volume Right cSH	787	1700	1428			
	0.01	0.10	0.00			
Volume to Capacity	0.01	0.10	0.00			
Queue Length 95th (m)	9.6		0.1			
Control Delay (s)		0.0				
Lane LOS	A	0.0	A			
Approach LOS	9.6 A	0.0	0.2			
Approach LOS	H					
Intersection Summary						
Average Delay			0.4			
Intersection Capacity Utiliz	zation		20.0%	IC	U Level	of Service
Analysis Period (min)			15			


	•	•	<b>†</b>	~	<b>&gt;</b>	<b>↓</b>
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		ĵ.			4
Traffic Volume (veh/h)	0	0	185	1	0	172
Future Volume (Veh/h)	0	0	185	1	0	172
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	0	0	215	1	0	200
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	416	216			216	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	416	216			216	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	597	829			1366	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	0	216	200			
Volume Left	0	0	0			
Volume Right	0	1	0			
cSH	1700	1700	1366			
Volume to Capacity	0.00	0.13	0.00			
Queue Length 95th (m)	0.00	0.13	0.00			
Control Delay (s)	0.0	0.0	0.0			
• • •		0.0	0.0			
Lane LOS Approach Delay (s)	A 0.0	0.0	0.0			
Approach LOS	0.0 A	0.0	0.0			
Apploach LOS	А					
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliz	zation		13.1%	IC	CU Level o	of Service
Analysis Period (min)			15			

	•	•	<b>†</b>	~	-	↓ ¯
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		1>			4
Traffic Volume (veh/h)	10	12	174	14	13	159
Future Volume (Veh/h)	10	12	174	14	13	159
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	11	13	189	15	14	173
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	398	196			204	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	398	196			204	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	98	98			99	
cM capacity (veh/h)	606	850			1380	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	24	204	187			
Volume Left	11	0	14			
Volume Right	13	15	0			
cSH	717	1700	1380			
Volume to Capacity	0.03	0.12	0.01			
Queue Length 95th (m)	0.03	0.0	0.01			
Control Delay (s)	10.2	0.0	0.7			
Lane LOS	В	0.0	Α			
Approach Delay (s)	10.2	0.0	0.7			
Approach LOS	10.2 B	0.0	0.1			
	D					
Intersection Summary						
Average Delay			0.9			
Intersection Capacity Utiliz	zation		29.1%	IC	CU Level of	of Service
Analysis Period (min)			15			



# **Appendix H – Left Turn Lane Warrant**

#### Exhibit 9A-19



AREAS OR URBAN AREAS WITH RESTRICTED FLOW

TRAFFIC SIGNALS MAY BE WARRANTED IN
"FREE FLOW" URBAN AREAS

